


GRABER MANUFACTURING, INC. 1080 UNIEK DRIVE WAUNAKEE, WI 53597 P(800) 448-7931, P(608) 849-1080, F(608) 849-1081 WWW.MADRAX.COM, E-MAIL: SALES@MADRAX.COM



Finn Installation Guide **CHECK LOCAL CODES**

Installation Guide Applies to The Following Madrax Bike Racks:

Finn

CONFIDENTIAL DRAWING AND INFORMATION IS NOT TO BE COPIED OR DISCLOSED TO OTHERS WITHOUT THE CONSENT OF GRABER MANUFACTURING, INC. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

There must be at least a six foot clear walkway from buildings to comply with the American with Disabilities Act. The bicycle rack cannot be located directly in front of a store entrance or exit, nor in a driveway. The bicycle rack cannot be located closer to the curb than two feet. Three feet from curb is ideal, although in certain circumstances, the distance may be greater.

The footprint of a bicycle is approximately 2 feet by 6 feet. Some handlebars can be as much as 30 inches wide.

- INSTALL BIKE RACKS ACCORDING TO MANUFACTURER'S SPECIFICATIONS. CONSULTANT TO SELECT COLOR (FINISH), SEE MANUFACTURER'S SPECIFICATIONS. SEE SITE PLAN FOR LOCATION OR CONSULT OWNER.